

**Texaa®**

Specification and data sheets

# **Stereo panels - special solutions**

<b>Stereo panels - special solutions</b>	p. 3
Specification	p. 4
Sizes and acoustic performance	p. 5
Fitting methods	p. 8
<b>Aeria - cleaning guidelines</b>	p. 10
Technical characteristics	p. 11

### **Production time**

4 to 8 weeks

### **Professionals to be consulted for fitting**

General fitters and carpenters

# Stereo panels - special solutions

Our special solutions provide the opportunity to customise products a little more than what is offered in our standard range.

These tried-and-tested variants provide reliable technical solutions which can be costed easily by your Texaa contact and delivered within four to eight weeks.

# Specification

The acoustic absorption is provided by **Texaa® Stereo** panels which consist of:

- a rust-proof steel frame
- fully recycled white AF1 wadding
- grey or black microporous cloth cladding
- a removable and machine-washable cover made of sound-transparent, **Maille Ronde (MR) Aeria fabric (330 g/m<sup>2</sup>)** which provides a run-resistant, antistatic and dirt-repellent covering on five or six faces

## Durability of the fabric cover

Performance of **Aeria 330 g/m<sup>2</sup> run-resistant fabric**

Protection against soiling:

**Hydro/Oleophobic**  $\geq 5$  (AATCC118 and AATCC193)

**Electrostatic properties**  $7.10^{10}\Omega$  (EN 1149-1)

## Acoustic performance

Stereo suspended panels 1,199 x 1,199 x 55 mm:

Equivalent absorption area A (m<sup>2</sup>) at mid-range frequencies: 2 m<sup>2</sup>

## European reaction to fire classification

Complete product: B-s2, d0

## Environmental characteristics

HQE: EPD (EN 15804) – Environmental and Health Product Declarations certified by AFNOR

LEED / BREEAM:

4 points for  $\left\{ \begin{array}{l} - \text{acoustic contribution} \\ - \text{certified EPD (EN 15804)} \\ - \text{very low VOC (Volatile Organic Compounds) and formaldehyde emissions.} \end{array} \right.$

Impact on climate change: 22.7 kg CO<sub>2</sub> eq /m<sup>2</sup>

Proportion of recycled components  $\geq 57$

## Cleaning

Vacuum cleaning, may be removed and refitted. Cover is removable and machine washable

## Guarantee

10 years

## Colours

Select from the 30 colours in the palette

Special colours available on request

## Common options

Embroidery option

Specific sizes on request


(width from 300 to 1,200 mm and length from 600 to 2,400 mm;  
please contact us for larger sizes)

# Sizes and acoustic performance


## Stereo panels - special solutions

Suspended under horizontal cables


Suspended overlapping on vertical cables



299 x 1,199 x 55 mm



299 x 1,799 x 55 mm



299 x 2,399 x 55 mm



599 x 1,199 x 55 mm



599 x 1,799 x 55 mm



599 x 2,399 x 55 mm



599 x 599 x 55 mm




1,199 x 1,199 x 55 mm




1,199 x 1,799 x 55 mm



1,199 x 2,399 x 55 mm



Ø 1,199 x 55 mm



1,199 x 1,199 x 1,696 x 55 mm

## Dimensions / weight / acoustic performance [specify]

Dimensions (mm)	Weight (kg)	Equivalent absorption area A (m <sup>2</sup> ) at mid-range frequencies
□ 299 x 1,199 x 55	4.3	-
□ 299 x 1,799 x 55	5.9	-
□ 299 x 2,399 x 55	7.2	-
□ 599 x 599 x 55	3.9	-
□ 599 x 1,199 x 55	5.5	1.06
□ 599 x 1,799 x 55	7.8	1.52
□ 599 x 2,399 x 55	9.6	2.03
□ 1,199 x 1,199 x 55	8	2.00
□ 1,199 x 1,799 x 55	12	2.86
□ 1,199 x 2,399 x 55	14.4	3.80
□ Round: diameter 1,199 x 55	8.6	1.62
□ Triangle 1,199 x 1,199 x 1,696 x 55	5.5	1.08

# Sizes and acoustic performance

## Stereo panels - special solutions

Suspended on vertical cables, against a wall

Mounted on vertical metal surfaces with magnets



299 x 1,199 x 55 mm



299 x 1,799 x 55 mm



299 x 2,399 x 55 mm



599 x 1,199 x 55 mm




599 x 1,799 x 55 mm



599 x 2,399 x 55 mm



599 x 599 x 55 mm




1,199 x 1,199 x 55 mm




1,199 x 1,799 x 55 mm



1,199 x 2,399 x 55 mm



Ø 1,199 x 55 mm



1,199 x 1,199 x 1,696 x 55 mm

## Dimensions / weight / acoustic performance [specify]

Dimensions (mm)	Weight (kg)	Equivalent absorption area A (m <sup>2</sup> ) at mid-range frequencies
□ 299 x 1,199 x 55	4.3	-
□ 299 x 1,799 x 55	5.9	-
□ 299 x 2,399 x 55	7.2	-
□ 599 x 599 x 55	3.9	-
□ 599 x 1,199 x 55	5.5	1.06
□ 599 x 1,799 x 55	7.8	1.52
□ 599 x 2,399 x 55	9.6	2.03
□ 1,199 x 1,199 x 55	8	2.00
□ 1,199 x 1,799 x 55	12	2.86
□ 1,199 x 2,399 x 55	14.4	3.80
□ Round: diameter 1,199 x 55	8.6	1.62
□ Triangle 1,199 x 1,199 x 1,696 x 55	5.5	1.08

## Stereo panels - special solutions

### As screw-mounted baffles



299 x 1,199 x 55 mm



299 x 1,799 x 55 mm



299 x 2,399 x 55 mm



599 x 1,199 x 55 mm



599 x 1,799 x 55 mm



599 x 2,399 x 55 mm




599 x 599 x 55 mm

### Dimensions / weight / acoustic performance [specify]


Dimensions (mm)	Weight (kg)	Equivalent absorption area A (m <sup>2</sup> ) at mid-range frequencies
□ 299 x 1,199 x 55	4.4	0.57
□ 299 x 1,799 x 55	6.1	0.79
□ 299 x 2,399 x 55	7.4	-
□ 599 x 599 x 55	4	-
□ 599 x 1,199 x 55	5.7	1.17
□ 599 x 1,799 x 55	8.2	1.67
□ 599 x 2,399 x 55	9.1	2.26

## Stereo panels - special solutions

### Suspended on vertical cables, as a canopy



1,199 x 2,446 x 55 mm



1,199 x 2,388 x 55 mm

### Dimensions / weight / acoustic performance [specify]

Dimensions (mm)	Weight (kg)	Equivalent absorption area A (m <sup>2</sup> ) at mid-range frequencies
□ Triangle 1,199 x 2.446	10.9	-
□ Trapezium 1,199 x 2.388	13.2	-


# Fitting methods

## □ Suspended under horizontal cables

Each **Stereo** panel is suspended under 2 horizontal cables (not supplied) using 4 vertical cables (diameter 1 mm, length 1,000 mm) made of galvanized steel, each fitted with a cross-shaped stainless steel cable clamp and an adjustable hook.

The cross-shaped cable clamp is compatible with horizontal cables 2 to 6 mm in diameter.

### □ Optional fabric covering for top face



Cross-shaped cable clamp



## □ Suspended overlapping from vertical cables

Each **Stereo** panel is suspended horizontally from the ceiling by means of vertical cables made of galvanised steel (diameter 1 mm, length 3,000 mm) fitted with a small cylindrical cover. Several panels can be positioned up and down the same cables, one above another. Covers are applied to the end of each cable, when they are installed.


Please specify configuration in a drawing.

### □ The option of covering the top face is recommended in two cases:

- when in the chosen configuration, the top face of the panels is visible
- the panels are close to one another (reflection of light)



Adjustable slider




Finishing cover

## □ Suspended on vertical cables against a wall

Each **Stereo** panel is suspended vertically from a rail using cables (diameter 1.5 mm, length 1,500 mm) made of galvanized steel, each fitted with a spherical end-piece. The rear of each panel is equipped with two adjustable sliders.

- White powder-coated aluminium rails, length 2,000 mm






□ **Mounted on vertical metal surfaces with magnets**

Each **Stereo** panel can be mounted on metal furniture or partitions using 8 mm-thick thick magnets.


NB: ensure that the support surface used is compatible with the magnets



□ **As a screw-mounted baffle**

Each **Stereo** panel is attached to a 20-mm high support rail secured to the ceiling with screws.

NB: Fitting/removal requires a 20-mm gap on one side of the panel.



The head engages in the rail screwed to the ceiling





□ **Suspended on vertical cables as a canopy**

Each **Stereo** panel is suspended from the ceiling at an angle of 7° from the vertical on cables made of galvanised steel (diameter 1 mm, length 1,000 mm) fitted with a small cylindrical cover and an adjustable eye hook with a latch. The panels are held in position with pairs of fixing tabs. The panels' upper surface is covered.

The canopies consist of:

- triangular panels
  - and/or trapezoid panels
  - and/or rectangular panels
- and form a convex or concave arrangement.

Please specify configuration in a drawing.



A 70-mm wide opening at the centre of the structure allows air and any technical equipment to pass through (light fittings, IT cabling, etc.).

# Aeria - cleaning guidelines

To protect the fresh colour of your **Aeria** fabric, we advise you to clean it regularly by:

- removing dust with a soft brush and vacuum cleaner
- using an absorbent cloth to soak up spilt liquids
- cleaning marks or stains quickly, before they have time to dry and become harder to remove

**Aeria** is treated with a water-repellent product, so any stains can usually be removed by gentle dabbing. Never rub the fabric.

**If a stain proves harder to remove, please follow the instructions below:**

## **For water-based liquids (tea, coffee, soft drinks, wine, etc.)**

If the stain has penetrated the fabric, use a vacuum cleaner to remove any dust from the soiled area. Then, rehydrate the stain by dabbing the marked area with one hand using a cloth dampened with clean water, and dry the area with the other hand using a dry, clean absorbent cloth. If the stain persists, repeat the process using water and a little soap.

## **For oil-based liquids**

Dab the stain with a clean cloth dampened with undiluted solvent-based cleaning fluid. Remember to fold the cloth frequently, so that the stain is always in contact with a clean part of the cloth's surface.

## **For semi-solid stains, such as butter, ketchup, etc.**

Remove any remaining solid material with a spatula and proceed with the cleaning method detailed above for oil-based liquids.

## **For dye-based stains (marker pen, biro, ink, etc.)**

Dab the stain with a clean cloth dampened with a solvent such as methanol. Remember to fold the cloth frequently, so that the stain is always in contact with a clean part of the cloth's surface.

**In order to avoid the formation of rings, clean stains and marks from the outside towards the middle, and then use a hair-dryer to speed up the drying process.**

# Technical characteristics

Definition	Stereo
<b>Fitting</b>	Suspended or screw-mounted
<b>Components</b>	<b>Aeria*</b> / fully recycled white AF1 wadding / grey or black microporous cloth / a rust-proof steel frame
<b>Colours</b>	30 colours
<b>Physical properties</b>	
<b>Light reflectance</b> (for Nacre (Pearly white) colour, MR 640)	81%
<b>Durability</b>	
<b>Mechanical properties</b>	
Abrasion resistance (EN 12947-2, number of rubs)	> 30,000
Fraying	none
Variations in dimensions under normal conditions of temperature and humidity	none
Colour fastness ISO 105-B02 (scale from 1 to 8)	≥ 5
Electrostatic properties (EN 1149-1)	> 7.10 <sup>10</sup> Ω
Hydro/oleophobic AATCC 118 and AATCC 193 (scale from 1 to 8)	≥ 5
Conditions of normal exposure	relative humidity between 30% and 75% and temperature between 10°C and 30°C
Conditions of exceptional exposure	relative humidity between 20% and 90% and temperature between 10°C and 30°C
Mechanical strength of the fastenings	15 kg /fixing point (DIN EN 12385-4)
<b>Health and safety</b>	
<b>Reaction to fire classification</b>	
Europe EN for complete product	B-s2, d0
United States ASTM	Class A
<b>Environmental characteristics</b>	
<b>Development of micro-organisms</b>	the materials used reduce the proliferation of house dust mites and micro-organisms
<b>HQE® High Quality Environmental standard</b> (standard EN 15804)	AFNOR-certified environmental product declaration
<b>VOC and formaldehyde emissions</b> (ISO 16000) French health labelling / in accordance with German protocol AgBB	A+ / compliant
<b>Contribution to LEED/BREEAM certification</b> – certified EPD – air emissions – acoustic contribution	4 points
<b>Impact on climate change</b>	22.7 kg CO <sub>2</sub> eq /m <sup>2</sup>
<b>Proportion of recycled components</b>	≥ 57 %
<b>Cleaning</b>	
Method	vacuum clean every one to five years, depending on conditions of use** cover is removable and machine-washable at 30°C, dry flat

\*Texaa®'s internationally patented **Aeria** sound-transparent fabric / \*\*refer to the cleaning and maintenance sheets

**Texaa®** is a privately owned company with a staff of fifty-five. Informed by continuous contact with designers and professionals in the building industry, we conceive, manufacture and distribute solutions to enhance the acoustic comfort of the spaces in which people live and work. **Texaa®** products are technically sophisticated, sensitive and hard-wearing. Their hallmark is the textile in which they are clad: **Aeria\*** is knitted in our workshop near Bordeaux in a palette of 30 colours. Since 1978, it has been our pride and delight to play our part in developing quality architecture in France, Europe, the US and beyond.

\* our sound-transparent textile with an exclusive **Texaa®** patent

## Updates at [www.texaa.co.uk](http://www.texaa.co.uk)

- - -

**Texaa®**  
textile, acoustics, architecture

**United Kingdom**  
Becket House  
1 Lambeth Palace Road  
London SE1 7EU

- - -

+44 (0) 20 7092 3435  
[contact@texaa.co.uk](mailto:contact@texaa.co.uk)  
[www.texaa.co.uk](http://www.texaa.co.uk)